
LW-MW-SW-FM STEREO RECEIVER with STEREO CASSETTE RECORDER and TURN-TABLE



SPECIFICATION

General

Slider Controls

Balance, Volume, Bass, Treble,

Rotary Controls

Push Buttons (Left to Right)

Front Sockets Rear Sockets

(Left to Right)

Consumption Amplifier.

Semi-Conductors Power Output

Output Impedance Frequency Response Treble Control Range Bass Control Range Gram input sens.

Tape input sens. Signal to Noise Ratio

Power Supply

Tuner FM. Coverage

FM. IF.

FM. Aerial Impedance FM. Sensitivity

FM. Sensitivity Multiplex (Seperation)

Tuning, Record level

St-Mono, ON-OFF, phono, Tape, LW, MW, SW. FM AFC/BEAT. CrO2

Headphones Jack, Stereo Microphone Aerials, AM(SW) FM to DIN Standard, Tape, Speaker Left.

130 Watts max.

45 transistors, 1 integrated circuit 18 diodes.

15 watts per channel @ 1% THD. 8 ohms per channel

15 Hz-20 KHz \pm 3 dB

@ 14 KHz = +10 dB to - 7 dB@ $60 \text{ Hz} = +10 \text{ dB to} \cdot 10 \text{dB}$ (a) 1 KHz = 5 mv for Rated Output @ 1 KHz = 300 mv for Rated Output

Better than - 45 dB

220 Volt AC 50 Hz. (240 volt. 50 Hz.)

88 MHz - 104 MHz

10.7 MHz 300 ohms

For S/N 30 dB = 5 microvolt.For 30 dB limiting = 28 microvolt.

Tuning Indicator AM LW Coverage

AM-SW Coverage

Sensitivity AM MW Coverage

Sensitivity

Speaker Right, Power, Fuse (500 MA).

AM-IF 460 KHz

Aerial LW-MW Ferrite Rod Aerial SW External Terminal

Tape Mechanism System Cassette, 4 Track, 2 channel horizontal POP-UP

Wow-Flutter 0.15 % Speed 4.75 cm/SEC

40 Hz 10,000 Hz \pm 6 dB Frequency Response

Cross Talk 35 dB S/N Ratio 50 dB Tane Counter Digital 80 KHz

Tape Bias and Erase Frequency

Level Control

CrO₂ Tape

switch to Chromdioxid performance. Stereo Recording with level meter.

Peaking Meter for acourate tuning.

150 KHz - 330 KHz

600 microvolt/meter

520 KHz - 1605 KHz

400 microvolt/meter

6 MHz - 10 MHz

20 micorovolt

NOTE: Due to the possibility of modifications from time to time, the right is reserved to supply goods which may differ slightly from those illustrated and described.

PARTS LOCATION & CIRCUIT BOARD DIAGRAM

TUNER, IF & MULTIPLEX CIRCUIT BOARD




Fig. 1






FIg. 2

BOTTOM VIEW


CASSETTE CIRCUIT BORRD




TOP VIEW Fig. 3



BOTTOM VIEW Fig. 4




TOP VIEW Fig. 5



BOTTOM VEIW Fig. 6

AUDIO CIRCUIT BOARD



TOP VIEW Fig. 7

BOTTOM VIEW Fig. 8




Fig. 9





Fig. 10



CIRCUIT DIAGRAM




Fig. 12

CIRCUIT DIAGRAM





Fig. 13

EXPLODED VIEW FOR CASSETTE MECHANISUM



MECHANICAL PARTS LIST(CASSETTE DECK)

NO.	PARTS NO.	DESCRIPTION	ŅO.	PARTS NO.	DESCRIPTION
1	Z4-2365	Screw, ⊕pan head M2×6	50	T4-5060	Brake lever spring
2	T4-6356	Wire holder	51	T4-6003	Brake lever
3	T4-8001	ERASE Head. T8004	52	Z4-2366	Screw, pan head M2.6×4
4	Z4-5032	Screw, ⊕pan head M2×3	53	Z4-3304	Spring washer 2.6S
5	T4-10215	Spring holder	54	Z4-2372	Screw, plate M2×3
6	Z4-5539	Screw, ⊕ lock type M2×6	55	T4-7515	Motor MH1-5R9B
7	Z4-5132	Washer, flat $2\phi \times 0.4$	56	T4-7074	Motor pulley 2 # 2200
8	TA3-998	Head base ass'y	57	T4-10688	Motor cushion rubber
9	T4-7821	Head base spring B.	58	T4-9314	REW. lever
10	TA2-1027	ASO mechanism ass'y	59	Z4-1414	Snap ring $2.5 \phi \times 0.4$
11	Z4-5077	Screw, \oplus SEMS (w/spring washer) pan head M2×5	60	T4-7853	Idler B lever spring
12	T4-5067	Head adjusting spring	61	TA4-9511	Idler B ass'y
13	Z4-1413	Snap ring $2\phi \times 0.4$	62	T4-10401	REW. lever spring B
. 14	Z4-1413	Snap ring $2\phi \times 0.4$	63	T4-7013	Timing safety lever
15	Z4-5551	Screw, \oplus lock type M2×5	64	T3-702	Brake plate operation lever
16	T3-8031	REC./PLAY Head WY-438ZT	65	T4-7846	FR. lever spring D
17	Z4-5077	Screw, \oplus SEMS (w/spring washer) pan head M2×5	66	T4-7077	Brake slider operation lever spring
18	Z4-1413	Snap ring $2\phi \times 0.4$	67	Z4-1412	Snap ring $4\phi \times 0.6$
19	TA4-10335	Pinch roller arm ass'y	68	Z4-1414	Snap ring $2.5 \phi \times 0.4$
20	T4-10359	Pinch roller spring	69	Z4-1413	Snap ring $2\phi \times 0.4$
21	T3-810	Tape counter	70	Z4-5137	Washer, flat type $2.5 \phi \times 0.1$
22	Z4-5062	Screw, \oplus SEMS (w/spring washer) pan head M2.6×5	71	TA3-985	Idler A ass'y
23	T4-10342	Counter mounting plate	72	TA4-9049	FR. lever ass'y
24	Z4-5064	Screw, ⊕SEMS(w/spring washer)pan head M3×6	73	Z4-5108	Washer, flat type $3.1\phi \times 0.5$
25	TA4-10323	Push button mechanism ass'y	74	T4-7563	Motor switch BSW-46B
26	T4-10348	Push button cam plate spring	75	Z4-5061	Screw, \oplus SEMS(w/spring washer)pan head M2.6×4
27	T4-5100	REC. lever spring	76	T4-10586	FF. lever
28	T4-10278	REC. lever A-1	77	T4-10360	Pause operation lever spring
29	Z4-5061	Screw, \oplus SEMS(\dot{w} /spring washer) pan head M2.6×4	78	Z4-1414	Snap ring $2.5\phi \times 0.4$
30	T4-10436	Head base shaft	79	TA4-7063	FF. operation lever ass'y
31	TA2-1085	Push button block ass'y TM-229	80	Z4-1414	Snap ring $2.5 \phi \times 0.4$
32	TA2-1084	Parts mounting frame ass'y	81	Z4-6304	Steel ball 2¢
33	T4-1395	Head base shaft spring	82	T4-7079	FF. operation lever spring
34	Z4-2366	Screw , \oplus pan head M2.6 $ imes$ 4	83	TA4-10458	Pause operation lever ass'y
35	Z4-3304	Spring washer 2.6S	84	Z4-1414	Snap ring $2.5 \phi \times 0.4$
36	T4-7016	Head slider pressure spring	85	Z4-5128	Washer, polyethylene $2.5 \phi \times 0.25$
37	Z4-5202	Steel ball 2.5ϕ	86	T4-10218	Pause lock plate
38	Z4-6304	Steel ball 2 ø	87	T4-7687	Pause lock plate spring
39	T4-9512	Reel shaft cap	88	T4-7072	Motor mounting parts
40	Z4-5141	Washer, polyethylene $1.6 \phi \times 6 \phi \times 0.25$	89	Z4-5111	Washer, flat type $2\phi \times 0.4$
41	TA4-7102	Reel base B ass'y	90	Z4-5069	Screw, ⊕SEMS plate M2.6×7
42	Z4-3304	Spring washer 2.6S	91	T4-7081	Tension arm spring
43	Z4-5202	Steel ball 2.5 ϕ	92	TA4-7062	Tension arm ass'y
44	T4-10341	Counter belt 1□×41.7φ	93	Z4-1414	Snap ring $2.5 \phi \times 0.4$
45	Z4-2366	Screw, pan head M2.6×4	94	TA4-1958	Flywheel ass'y
46	Z4-5064	Screw, ⊕SEMS(w/spring washer)pan head M3×6	95	T4-7070	Main belt 1.2□×78.3φ
47	T4-7016	Head slider pressure spring	96	T4-7868	Flywheel holder plate
48	T4-10497	Cassette pressure spring	97	T4-7869	Flywheel adjust screw
49	Z4-1414	Snap ring $2.5\phi \times 0.4$	98	Z4-5063	Screw, ⊕SEMS(w/spring washer)pan head M2.6×6

11

TROUBLE SHOOTING CHART

SYMPTOM	CAUSE	REMEDY
	(2) In case of faulty recording	
	 Insufficient bias. Excessive recording level. Poor tape. 	 Adjust VR-701 and VR-702 Check with recording circuit. Try new tape.
Imperfect erasing	1. Dirty erase head or cassette tape.	 Clean by soft cloth with alchohol, or try new tape.
	Faulty erase head or disconnection of lead wires.	Solder disconnected wire or replace faulty head.
	3. Faulty OSC circuit.	3. Check and replace OSC. circuit parts
VU meter Inoperative	1. Faulty SW 10-4	1. Replace SW-10-4 if neccessary.
	2. Faulty VU meter.	2. Replace meter.
	Disconnection or short circuit of lead wires from meter.	3. Solder or replace wires.
	4. Faulty VU meter AMP circuit parts.	4. Replace meter AMP circuit parts.
Insufficient Volume	1. Dirty R/P head of cassette tape.	 Clean by soft cloth with alchohol, or try new tape.
	2. Faulty amplifier.	2. Check and replace parts.
	3. Improper angle of R/P head.	3. Adjust angle.
	4. Insufficient sensitivity of R/P head.	4. Replace head.
Noise	(1). Noise is heard while motor stops.	
	1. Faulty parts (Transistor. Resistor etc.) on amplifier.	1. Replace faulty parts.
	2. Faulty Rec/Play select switch.	2. Replace switch.
	(2). Noise is heard when tape is being playback.	
	1. Faulty motor.	1. Replace motor.
	(3). Noise is heard when recording.	
	1. Magnetized head.	1. Take magnetism off with eraser.
·	2. Faulty motor.	2. Replace motor.

DIAI CORD STRINGING





Fig. 15

TROUBLE SHOOTING CHART

SYMPTOM	CAUSE	REMEDY
Inoperative	 AC Plug not inserted properly. Faulty motor switch. Defective remote control jack. Defective remote control switch. inside microphone. 	 Insert AC plug properly. Adjust motor switch. (SW11) Adjust or replace jack if necessary. Replace microphone.
No Fast Forward	1. F.F. pulley slippage.	1. Clean by soft cloth with alchohol.
	2. Defective F.F. pulley.	2. Replace F.F. pulley.
No Rewind	1. Rew. roller slippage.	 Clean by soft cloth with alchohol.
	2. Defective Rewind. roller.	2. Replace Rewind. roller.
No Playback	 Motor pulley slips against flywheel. Pinch roller slippage. 	 Clean by soft cloth with alchohol. Clean by soft cloth with alchohol.
	Reel frange slips against take-up pulley.	3. Clean by soft cloth with alchohol.
Excessive wow and flutter	 Faulty flywheel. Faulty reel frange rubber. Reel frange rubber slippage. 	 Replace flywheel. Replace reel frange Clean by soft cloth with alchohol.
	4. Capstan slippage.	4. Clean by soft cloth alchohol.
	5. Dirty pinch roller.	Clean by soft cloth with alchohol.
	6. Dirty drive belt.	Clean by soft cloth with alchohol.
Audio Inoperative	 Faulty slide switch. Faulty amplifier. Disconnect speaker lead wire or voice coil. Faulty headphone jack. 	 Replace slide switch. Check and replace faulty parts. Solder disconnected parts or replace speaker. Replace headphone jack.
Faint or Distorted Audio	1. Faulty amplifier.	1. Check and replace faulty parts.
Does not record, reproduce OK	 Defective microphone. Faulty OSC circuit. Faulty slide switch. 	 Replace microphone. Check OSC, circuit. Replace slide switch.
Poor Tone Quality	·· Note: Check if recording caused poor tone quality by playing back pre-recorded tape.	
	(1) In case of faulty playback:	
	1. Dirty R/P head or cassette tape.	 Clean by soft cloth with alchohol, or try new tape.
	 Defaced R/P head. Improper angle of R/P head. Faulty parts on amplifier. 	 Replace head. Adjust anale. Replace faulty parts.

MECHANICAL ADJUSTMENTS



ALIGNMENT OF CASSETTE TAPE AMPLIFIER

1. Tape Speed:

Reproduce test tape, MTT-111 (3 KHz) and check if speed deviation be within $\pm 2.5\%$. If not, adjust semi-fixed resistor used for speed adjustment inside cassette motor.

2. Head Azimuth:

Reproduce test tape, MTT-113B(8KHz), and adjust azimuth alignment screw

1) to obtain maximum output level and 2) to read both L & R level within 3dB.

3. Recording Signal Level:

- a) Stop oscillation of the receiver by cutting power supply to cassette OSC circuit of the set or shorting two terminals of errase head.
- b) Add 1000 Hz Recording Signal:

For finished units, add the signal to TB (tape input); for semi-finished ones, add the signal to terminals No. 4 & No. 9 of E PCB(cassette PCB).

Then adjust the input so as to be reading of No. 3 & No. 8 terminals 0.28 mV/10 ohm (28.luA).

c) Adjust VR502 so that pointer of the receiver level meter to show 0 UV.

4. Recording Bias:

With an operation of OSC circuit, set C_TO_2 "ON" position. Apply potential meter onto No. 4 & No. 8 terminals of E PCB, and adjust the voltage by rotating VR701 & VR702 to read 6 mV/10 ohm (600 uA). Record on MTT-505 (chrome tape) the signal with level below-10 dB from 0 UV. Reproduce the signal and check if the signal at 8000 Hz to be within -6dB against 0 dB at 1000 Hz.

If the signal be over -6dB, re-adjust so that signal to be within -6dB by reducing bias current. Be surethat record & play distortion at 0 UV should not be less than 5% by this adjustment.

5. Adjustment of an operation of noise reduction circuit.

5 - 1

- a) Reproduce MTT-112 (0 dB at $333\,Hz$).
- b) Speaker output level to be adjusted to 500 mW.
- c) Add 10 KHz signal onto both terminals of recording & playback heads.
- d) Adjust the level (10 KHz signal) to read below -45dB from the speaker output level of MT-112, and then adjust by VR801 to the point where output signal wave shows sudden increase.
- 5-2 Or, reproduce noise of blank tape of MTT-505. Observing its noise by oscilloscope, and adjust VR801 to the point where the noise at high-end is just about to increase.

ALIGNMENT OF POWER AMPLIFIER CIRCUIT

Adjustment of Base Bias of output transistor

Add $10\,\mathrm{KHz}$ signal of which output voltage can obtain $10\,\mathrm{W}/4$ ohm to TB (tape input) terminal, and observe its wave (of $10\,\mathrm{W}/4$ ohm) by wide-band oscilloscope.

Adjust VR205 & VR305 to the point where overcross distortion begins to disappear. Be sure that the output level of residual hum should be less than 3 mV during this adjustment.

ELECTRICAL & MECHANICAL PARTS LIST

ELECTRICAL PARTS LIST

SYMBOL NO.	DESCRIPTION DESCRIPTION	SYMBOL NO.	DESCRIPTION		SYMBOL NO.	DESCRIPTI	ON -	
Q 101.102.105 Q 106.107	Transistor 2SC839H	R 157	* * 2.7KΩ		R 505	Resistor 1/4W	4.7ΚΩ	
Q 103.108	⋄ 2SC839F	R 158	* * 27 KΩ		R 506	, ,	3.9 KΩ	1
Q 104	✓ 2SC839F, H	R 159	Resistor 1/4 W 22KΩ		R 507	* *	15 ΚΩ	1
Q 504 - 505	∞ 2SC945P	R 160	» » 22KΩ		R 508	, ,	10ΚΩ	1
Q 504 505 664 805 Q 506 802 803 Q 502 503 Q 502 503		R 161	* * 22KΩ		R 509	, ,	120 ΚΩ	1
Q 302 503	✓ 2SC945P,Q	R 162	* * 22KΩ		R 510	, ,	10KM	1
Q 109.701.702	2SC945P, Q, R	R 201	Resistor 1/4W 3.3KΩ		R 511	* *	10 Κ Ω	1
Q 207 .307	✓ 2SC815L	R 202	* * 220KΩ		R 512	, ,	100ΚΩ	
Q 402	2SC1096L, M	R 203	» » 18KΩ		R 513	* *	820 ΚΩ	
Q 205.305	2SC1449L, M	R 204	» » 560 K Ω		R 514	, ,	68KΩ	
Q 202.203.302.303 501.601.801	✓ 2SC1648E	R 205	* * 100 Ω		R 515	* *	5.6 ΚΩ	
Q 201 . 301	→ 2SC1648ES	R 206	* * 33KΩ		R 516	<i>"</i> , "	1ΚΩ	
Q 206.306	∞ 2SA539L	R 207	* * 470KΩ		R 517	, ,	10ΚΩ	
Q 204.304	∞ 2SA733R	R 208	* * 820KΩ		R 518	, ,	2.7ΚΩ	
Q 401	2SA733P, Q, R	R 209	* * 2.7KΩ		R 519	, ,	2.7ΚΩ	
Q 208.209 308.309	⋄ 2SD 288L	R 210	. * · · · · · · · 220 Ω		R 520	* *.	820KΩ	
iC 1	Integrated circuit #PC554C	R 211	* * 22KΩ		R 521	, ,	820KΩ	
D 101.103.104	Siliana Diada 10010	R 212	* * 1.5KΩ		R 522	. , ,	2.2ΚΩ	
D 101.103.104	Silicon Diode 1S2473 Vari-cap Diode 1S2139B	R 213	* 2.2KΩ	l	R 523	* *	10Ω	
D 102 D 105 . 501	Vari-cap Diode 1S2139B Germanium Diode 1S188AM	R 214	, , 470KΩ		R 524	" "	.18U	1
D 107 . 108 . 109 D 801 . 802		R 215	″ ″ 15ÔΩ		R 601	Resistor 1/4W	56 ΚΩ	1
D 401	* * 1S188FM1 Zener Diode RD10EB	R 216	* * 10 K Ω		R 602	, ,	1800	1
D 401 D 402	/ RD12EB	R 217	* * 100 Ω		R 603	, ,	18KO	l
D 201 . 202	Silicon Varistor DS442	R 218	* * 22KΩ	l	R 604		150KΩ 4.7KΩ	
D 403 . 404 D 405 . 406	Rectifying Diode 1N4002(or SR1K2)	R 219	* * 1.8KΩ		R 605	, ,	4.7KΩ 2.9KΩ	
R 101	Resistor 1/4W 560 Ω	R 220	* * 22KΩ		R 606	, ,	3.9 KΩ	
R 102	» ° 5.6KΩ	R 221	* * 2.7KΩ		R 607	, ,	10ΚΩ 15ΚΩ	
R 103	» » 18KΩ	R 222	* * 1 KΩ	.	R 608 R 609	, ,	15 ΚΩ 120 ΚΩ	
R 104	« 47 Ω	R 223	* 1.5KΩ			, ,	10ΚΩ	
R 105	* 10KΩ	R 224	γ 4.7 Ω		R 610	, ,	10ΚΩ	
R 106	* * 4.7KΩ	R 225	~ ~ 330 Ω		R 611	, ,	10KΩ 100KΩ	
R 107	" " 1KΩ	R 226	» » 330 Ω		R 612	, ,	820KΩ	
R 109	« « 1.8KΩ	R 227	» 4.7 Ω		R 613	, ,	68 KΩ	
R 110	« « 10KΩ	R 228	ν IW 0.47 Ω	ļ	R 614		5.6ΚΩ	
R 111	»	R 229	» 1/4W 1KΩ		R 615 R 616	* *	1ΚΩ	
R 112	« « 27KΩ	R 230	* * 1.5KΩ		R 617	, ,	10ΚΩ	
R 113	» » 82KΩ	R 231	* * 470 Ω		R 618	, ,	2,7ΚΩ	
R 114	* * 1.5KΩ	R 232	* * 1.5KΩ		R 619	, ,	2.7ΚΩ	
R 115	* 100KΩ	R 233	" 1 W 0.47 Ω		R 620	, ,	820 KΩ	
R 116	« • 10 KΩ	R 234 R 301			R 623	, ,	10Ω	
R 117	* 4.7KΩ	R 302	Resistor 1/4W 323KΩ		R 701	Resistor 1/4W	10 ΚΩ	
R 118	» « 1KΩ	R 303	* * 18KΩ	.	R 702	,	3.3KΩ	
R 119	* * 1KΩ	R 304	, , , 560 K Ω		R 703	, ,	10Ω	
R 120	" " 100 Ω	R 305	, , 100 Ω		R 704	4 *	10Ω	
R 121	* * 2.7KΩ	R 306	* * 33KΩ		R 705	* *	10Ω	
R 122	* 10ΚΩ	R 307	* * 470 K Ω		R 706	, ,	47Ω	
R 123	» « 22KΩ	R 308	« « 820KΩ		R 801	Resistor 1/4W	82 ΚΩ	
R 124	»	R 309	* * 2.7KΩ		R 803	* *	1ΚΩ	
R 126	» « 100 Ω	R 310	, , 220 Ω		R 804	* *	5.6 K Ω	
R 127	, 220 Ω	R 311	» » 22KΩ		R 805	* *	2.2 ΚΩ	
R 128	« « 1KΩ	R 312	* * 1.5 KΩ		R 806	, ,	33 KΩ	
R 129	* 220 ΚΩ * 47 ΚΩ	R 313	* * 2.2 KΩ		R 807	, ,	100 ΚΩ	
R 130 R 131	 47KΩ 8.2KΩ 	R 314			R 901	Resistor 1/4W	100 KΩ	
R 131	* 0.2KΩ	R 315	, , 150 Ω		R 902	* *	100ΚΩ	
R 132	*	R 316	* * 10 KΩ		R 903	* 1 W	220Ω	
R 134	* * 27KΩ	R 317	* * 100 Ω		R 904	, , ,	220Ω 18Κ Ω	
R 135	* * 8.2KΩ	R 318	» » 22 ΚΩ		R 905	″ 1/4 W	18ΚΩ 18ΚΩ	
R 137	* * 560 Ω	R 319	* * 1.8KΩ		R 906	, ,	27K Ω	
R 138	, , 1KΩ	R 320	» » 22KΩ		R 907	, ,	27 ΚΩ	
R 139	* * 5.6KΩ	R 321	»		R 908 R 913	Resistor 1W	10Ω	
R 141	* * IKΩ	R 322	* * 1 KΩ			Resistor 1W	1077	
R 142	* * 1KΩ	R 323	″ ″ 1.5KΩ		R 914			
R 143	* * 10KΩ	R 324	° 4.7 Ω		C 101 C 102	Ceramic Capacitor	20 p F 10 p F	
R 144	» » 10KΩ	R 325	* 1/4 W 330 Ω		C 102 C 103	,	10 p F 0.022 μF	
R 145	» « 470KΩ	R 326	» « 330 Ω		C 103 C'104	,	0.022 μF 0.022 μF	
R 146	» « 1KΩ	R 327	* * 4.7 Ω		C 104 C 105	,	0.022 μr 30 p F	
R 147	» « 100KΩ	R 328	* 1 W 0.47 Ω		C 105 C 106	,	30 p F	
R 148	* * 56KΩ	R 333			C 106		apr 3pF	
R 149	* * 22KΩ	R 334	Resistor 1/4W 4/0KH Resistor 1/4W 56 \Omega		C 107 C 108	,	ορ ι 0.01 <i>μ</i> F	
R 150	« « 22KΩ	R 401 R 402	Resistor 1/4 W 30 Ω		C 108 C 109	*	0.01 µF 0.022 µF	
R 151	" " 220 · Ω	R 404	, 470 Ω		C 109 C 110	,	1.3pF	
1	Resistor 1/4W 47 Ω	R 501	Resistor 1/4W 56KΩ		C 110	,	20 p F	
R 152	* 4.7 KΩ		* * 180 Ω		11 1	,		
R 152 R 153	•	 I Brane i					SUDE	
	* * 3.9KΩ	R 502		.	C 112 -		50 p F 20 n F	
R 153	•	R 502 R 503 R 504	* 18ΚΩ * 150ΚΩ		C 112 - C 113 - C 114 -	. ,	50 р F 20 р F 20 р F	

YMBOL NO.	DESCRIPTION	1	SYMBOL NO.	DESCRIPTION		SYMBOL NO.	DESCRIPTION
C 115	,	10 p F	C 171	Ceramic Capacitor 0.001 µ F		C 407	Ceramic Capacitor 0.022 µF
C 116	Ceramic Capacitor	0.022 µF	C 172	ν ν 0.001μF		C 408	ν 0.022 μF
C 117	,	0.022 µF	C 201	Eleotrolytic Capacitor 4.7μF/10~25V		C 409	φ 0.022 μF
C 118	"	0.022 µF	C 202	Mylar Capacitor 0.022 µF	l II	C 410	Mylar Capacitor 0.1 μF
C 119	,	0.022 µF	C 203	Ceramic Capacitor 100 pF	1 11	C 411	Ceramic Capacitor 0.022 µF
C 120	"	10pF	C 204	Electrolytic Capac.tor 4.7μF/10~25V		C 412	Electrolytic Capacitor 220 µ F / 10 V
C 121	*	82pF	C 205	Ceramic Capacitor 40p F		C 501	Electrolytic Capacitor 4.7 µF/10~25V
C 123	"	20 p F	C 206	Electrolytic Capacitor 4.7µF/10~25V		C 502	Ceramic Capacitor 50 p F
C 124	*	0.039 µF	C 207	Ceramic Capacitor 470p F		C 503	Electrolytic Capacitor 4.7μ F/10~25V
C 125	Mylar Capacitor	0.022 µF	C 208	Electrolytic Capacitor 4.7μF/10~25V		C 504	Ceramic Capacitor 0.01 µF
C 126	Ceramic Capacitor	0.022 µF	C 209	Ceramic Capacitor 0.0022 µF		C 505	Electrolytic Capacitor 4.7μF/10~25V
C 127	"	0.022 µF	C 210	Mylar Capacitor 0.015 μF		C 506	Ceramic Capacitor 0.0068 µF
C 128	*	0.039 µF	C 211	€eramic Capacitor 0.01 µF		C 507	» 0,0047 μF
C 129	"	82 p F	C 212	Mylar Capacitor 0.1 µF	1	C 508	° 0.01 μF
C 130	"	3p F	C 213	Electrolytic Capacitor 4.7μF/10~25V		C 509	√ 100 pF
C 131	*	39pF	C 214	Ceramic Capacitor 470p F		C 510	Electrolytic Capacitor 4.7µF/10~25V
C 132	Polystyrene Capacitor	3300 p F	C 215	Electrolytic Capacitor 1µF/10~50V		C 511	4.7μF/10~25V
C 133	,	270pF	C 216	» 1μF/10~50V	l i	C 512	$^{\circ}$ 4.7 μ F/10~25V
C 134	"	100 p F	C 217	Ceramic Capacitor 0.0015µF		C 513	, 1μ F/10~25V
C 135	Ceramic Capacitor	0.022 µF	C 218	Electrolytic Capacitor 220µF/10V		C 514	Ceramic Capacitor 0.022 µF
C 136	Electrolytic Capacitor 4.	7µF/10∼25V	C 219	Ceramic Capacitor 470p F	1	C 515	Electrolytic Capacitor 220µ F /10V
C 137	Mylar Capacitor	0.1µF	C 220	25p F		C 516	220μ F /10V
C 138	Ceramic Capacitor	0.022 µF	C 221	Electrolytic Capacitor 47μ F / 16V		C 517	Ceramic Capacitor 0.022 µF
C 139		220µ F /10V	C 222	° 100μ F /10V		C 518	, 100pF
C 140	Ceramic Capacitor	0.022 µF	C 223	% 100µF / 10V		C 519	Mylar Capacitor 0.01,4 H
C 141	"	0.022 µF	C 224	* 1000μ F / 16V	ļ	C 601	Electrolytic Capacitor 4.7 \$\mu \text{F}/10-25\end{a}
C 142	*	0.022 μF	C 301	Electrolytic Capacitoc 4.74F/10-25V	1	C 602	Ceramic Capacitor 50 p I
C 143	" .	0.022 µF	C 302	Mylar Capacitor 0.022 µF		C 603	Electrolytic Capacitor 4.7μF/10~25
C 144	,	0.022 μF	€ 303	Ceramic Capacitor 100 pF		C 604	Ceramic Capacitor 0.01 µl
C 145	Mylar Capacitor	0.039 µF	C 304	Electrolytic Capacitor 4.7µF/10~25V		C 605	Electrolytic Capacitor 4.7μF/10~25V
C 146	Ceramic Capacitor	3 p F	C 305	Ceramic Capacitor 40p F		C 606	Ceramic Capacitor 0.0068 #1
C 147	"	130 p F	C 306	Electrolytic Capacitor 4.7μF/10~25V		C 607	φ 0,0047 μ1
C 148	Electrolytic Capacitor 4.		C 307	Ceramic Capacitor 470p F		C 608	ο. 01 μ1
C 149	Ceramic Capasitor	0.001 µF	C 308	Electrolytic Capacitor 4.7μF/10~25V		C 609	∞ 100 p1
C 150	,	0.001 µF	C 309	Ceramic Capacitor 0.0022 µF		C 610	Electrolytic Capacitor 4,7µF/10-25
C 151	*	0.022 µF	C 310	Mylar Capacitor 0.015 µF		C 611	* 4.7μF/10~25
C 152	*	0.022 µF	C 311	Ceramic Capacitor 0.01 µF	1	C 619	Mylar Capacitor 0.01µ1
C 153 -	Electrolytic Capacitor 4.		C 312	Mylar Capacitor 0.1 µ F		C 701	Polystyrene Capacitor 100 p
C 154	Ceramic Capacitor	0.022 µ F	C 313	Electrolytic Capacitor 4.7µF/10~25V	,	C 702	∞ 100 p
C 155	*	0.022 µ F	C 314	Ceramic Capacitor 470p F	1	C 703	ø 1000 p
C 156	"	220pF	C 315	Electrolytic Capacitor 1/2 F / 10~50V		C 704	
C 157	Electrolytic Capacitor 4.		C 316	/ μF/10~50V		C 705	Ceramic Capacitor 0.01 µ
C 158	Ceramic Capacitor	330 p F	C 317	Ceramic Capacitor 0.0015 µF		C 706	ν 0.01 μ
C 159	Electrolytic Capacitor 4.		C 318	Electrolytic Capacitor 220µ F / 10V		C 707	Electrolytic Capacitor 100 \mu F/10-16
C 160		.7μF/ "	C 319	Ceramic Capacitor 470p F		C 708	Ceramic Capacitor 0.022µ
C 161		.7μF/ "	C 320	∞ 25p F		C 801	Ceramic Capacitor 470 p
C 162	Ceramic Capacitor	0.0047 µF	C 321	Electrolytic Capacitor 47µF / 16V		C 802	⋄ 470 p
C 163	"	Зр F	C 401	Electrolytic Capacitor 47 μ F /10V		C 803	% 25p i
C 164	*	3p F	C 401	Ceramic Capacitor 0.022 µ F	1	C 804	Aluminum solid Capacitor 0.47 μ
C 165	* -	10p F	C 402 C 403	* 470μ F / 25V		C 805	Ceramic Capacitor 0.001 μ
C 167	,	0.0047 µF	C 403	³ 2200μ F / 25V		C 806	Aluminum solid Capacitor 0.47 μ
C 168	,	0.001 µF	C 404 C 405	2200μF / 25V		C 807	Ceramic Capacitor 0.01 μ
C 169	″	0.001 µF	C 405 C 406	Ceramic Capacitor 0.022 µF		C 808	σ 0.01 μ
C 170	"	390pF	SYMBOL	octume oupdown	1	SYMBOL	PARTS NO. DESCRIPTION
NO.	PARTS NO. DESC	RIPTION	NO.	PARTS NO. DESCRIPTION		NO.	PARTS NO. DESCRIPTION
Т 101	12-0004 FM antenna	coil ass'v	TC 101	TPB-11 Trimmer		JK 4	* AM ANT. *
T 101	HF 149S FM IFT 1s		TC 102	TPA-11 *		JK 5	CS-253-1-2 MIC *
T 102	HF-149S * 2nd		TC 103	TPB-11 *		JK 6	LJ035 Headphone jack
T 104	HF-118 / 3re		TC 104	TPB-11 *		JK 7	2PDIN LB3 Speaker jack Left " " Right
T 105	11-0008 KW antenna	coil ass'y	TC 105	TPA-11 .		JK 8	l " .
T 106	11-0007 LW,MW ant	enna coil ass'y	TC 106	TPB-11 *		HD 1 HD 2	WY438ZT Recording tape head T4·8001 Erasing bead
Т 107	09-0013 KW OSC.	coil	SW1-9	26-0023 9-P push switch		HD 2 M 1	HM1-5R9B Cassette motor
T 108	S67-724 MW *		SW 10	26-0032 Recording switch 1-1 Cassette motor switch	h	ME 1	BO7A35R Tuning level meter
T 109	S67-723 LW *		SW 11 SW 12	1-1 Cassette motor switc 285V (15)/1-N Power switch	"[ME 2	BO7A34R Rec. level meter
T 110	H11-137S AM IFT 1s 893 FM IFT 4t		SW 12 SW 13	VR 204 MONO STEREO switch	h	FU 1	2AT Fuse
T 111 T 112	893 FM IFT 4t 14S-569 AM IFT 2nd		VR 201	50KΩ A×2 Treble Volume		FU 2	2AT *
T 113	l I	S. Primary	VR 202	% Bass %		FU 3	1A F-7142 "
T 114	HF-085BS /	Secondary	VR 203	% Sound %		FU 4	T500mA "
T 115	H1-144S AM IFT 3r		VR 204	50KΩW Balance «		OFU 5	(1.6AT FUSE)
T 701	S67-721 Cassette OS		VR 205	100ΩB half fixed resistance		○FU 6	(, ,)
* T 901	Power tran		V R 305	*		PL 1	Dial lamp .
	13-0007 FM RF coi	1 [VR 502	50 ΚΩ Β		PL 2	,
1.101	14-0004 FM IF Tra	p coil	.VR 701	"		PL 3 PL 4	
				* *	1	PI 1	. 7
1.101	13-0008 FM OSC c	oil	VR 702				Motor lump
L 101 L 102		oi!	VR 801	500Ω B ″		PL 5	Meter lamp
L 101 L 102 L 103	13-0008 FM OSC c	Block coil					Meter lamp " FM stereo indicator lamp

* T 901 · 220V · 06-0012BS 240V · 06-0012C